

## IoT Wireless Temperature, Relative Humidity, CO2 and atmospheric pressure Datalogger with built-in GSM modem and Flat Rate SIM Card

code: U4440Msim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud.

loT Datalogger is designed to record temperature, humidity, atmospheric pressure and CO2 from built-in sensors. In case of exceeded set limits email is sent from the  $\underline{\mathsf{COMET}}$  Cloud.

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard.** 

## **Technical data**

TEMPERATURE SENSOR	
Measuring range	-20 to +60 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	± 1.8 % RH
Resolution	0.1% RH
DEW POINT	
Measuring range	-90 to +60 °C
Accuracy	$\pm 1.5$ °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
CO2 SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50ppm +3% from reading) at 25°C and 1013hPa
Resolution	1 ppm
ATMOSPHERIC PRESSURE SENSOR SENSOR	
Measuring range	600 to 1100 hPa
Accuracy	±1.3 hPa at 23 °C from 800 to 1100 hPa
Resolution	0.1 hPa
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	internal sensor for temperature, humidity, CO <sub>2</sub> and atmospheric pressure
Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval	adjustable from 1 s to 24 h
Display and alarm refresh	adjustable 1 s, 10 s, 1 min

Recording mode	noncyclic - data logging stops after filling the
	memory cyclic - after filling memory oldest data is
	overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	battery SONY Lilon 5200mAh
Protection class	IP20
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 250 g
Warranty	3 years