

# Wöhler DP 600 Leakage Tester



## Technical data

Pressure	Range	±7.000 Pa
	Resolution	0,1 Pa from 0...900 Pa 1 Pa from 900 Pa
	Accuracy	±0,5 Pa, ±2,5 % f.m.
Volume flow without adapter	Range	0...200 Nm <sup>3</sup> /h
	Resolution	0,1 Nm <sup>3</sup> /h
	Accuracy	±2,5 Nm <sup>3</sup> /h, ±5 % f.m.
Volume flow with adapter 3,0	Range	0...10 Nm <sup>3</sup> /h
	Resolution	0,01 Nm <sup>3</sup> /h
	Accuracy	±0,05 Nm <sup>3</sup> /h, ±5 % f.m.
Volume flow with adapter 0,3	Range	0,10...18 NL/min
	Resolution	0,01 NL/min
	Accuracy	±0,05 NL/min, ±5 % f.m.
General information	Power Supply	110...230 V, 50...60 Hz
	Size	33 x 36 x 15 cm
	Weight	9,2 kg

**WÖHLER**

Wöhler Technik GmbH  
Headquarters Germany

Wöhler-Platz 1 · 33181 Bad Wünnenberg

[www.woehler-international.com](http://www.woehler-international.com)