

Level measurement

Guided wave radar **MOLOS**
wave **1**

Yo-Yo sensing systems **MOLOS**
bob **2**

Visualization **MOLOS**
visu **3**

Rotation **MOLOS**
roto **4**

Membrane **MOLOS**
membran **5**

Level indicator

Vibration **MOLOS**
vibro **6**

Microwave barrier **MOLOS**
barrier **7**

Pendulum **MOLOS**
pendu **8**

Coding **MOLOS**
code **9**

Hose couplings

Limit switch **MOLOS**
switch **10**

Swivelling lever **MOLOS**
swing **11**

Lockable couplings **MOLOS**
lock **12**

Overload protection **MOLOS**
safe **13**

Silo filling device **MOLOS**
safe **14**

Bulk solids handling

Pressure device **MOLOS**
pressdec **15**

Microwave flow sensor **MOLOS**
flow **16**

Pinch valves **MOLOS**
valve **17**

MOLOS
lock



Advantages of lockable couplings:

- higher safety
- robust locking mechanism
- prevent from unauthorized access
- different locking systems
- easy handling

Lock and locking systems for Storz couplings.

(other coupling systems on request)

with cylinder lock



with commodity padlock

with pneumatic locking



Selection list

Storz couplings with cylinder lock

Hose couplings

Type

KS-SZ052G038AL
KS-SZ052U038AL

KS-SZ052G042AL
KS-SZ052U042AL

KS-SZ052G052AL
KS-SZ052U052AL

KS-SZ065G052AL
KS-SZ065U052AL

KS-SZ065G065AL
KS-SZ065U065AL

KS-SZ065G075AL
KS-SZ065U075AL

KS-SZ075G075AL
KS-SZ075U075AL

KS-SZ075G080AL
KS-SZ075U080AL

KS-SZ090G090AL
KS-SZ090U090AL

KS-SZ100G100AL
KS-SZ100U100AL

KS-SZ110G100AL
KS-SZ110U100AL

KS-SZ110G110AL
KS-SZ110U110AL

Blank caps

Type

KS-SZ052G-B-AL
KS-SZ052U-B-AL

KS-SZ065G-B-AL
KS-SZ065U-B-AL

KS-SZ075G-B-AL
KS-SZ075U-B-AL

KS-SZ090G-B-AL
KS-SZ090U-B-AL

KS-SZ100G-B-AL
KS-SZ100U-B-AL

KS-SZ110G-B-AL
KS-SZ110U-B-AL

G = simultaneous locking
U = unequal locking

Couplings made of aluminium alloy

bold = **Standard**
* = at stock

further size on request

further materials on request

further designs on request

Padlock, height of bail 80 mm

Padlock installed in fixed coupling and blank cap type Storz

KS-VS080-GE simultaneous locking
KS-VS080-UE unequal locking

Substitutional padlock

KS-VS080-G simultaneous locking
KS-VS080-U unequal locking

Pneumatic locking

Locking installed in fixed coupling type Storz

KVPZ012-020MV-C5E 24 V DC

Substitutional cylinder complete with solenoid

valve 24 V DC
K-PZ012-020MV-C5

We provide deliveries, services and offers exclusively on the basis of our General Terms and Conditions that are available for viewing and download at www.mollet-level.com.

Technical alteration rights reserved.

