

# Wöhler BC 600 Blower Check



## Technical data

Differential pressure	Measurement range	-100...100 Pa
	Resolution, display	0,1 Pa
	Accuracy	Max of 0,25 Pa or 1 % of meas.
Air flow rate at 50 Pa (extrapolated)	Measurement range	15...6.000 m³/h
	Resolution, display	0,1 m³/h
	Accuracy	±5 % or 1,5 m³/h (higher value applies)
Air temperature	Measurement range	-20...+50 °C
	Resolution, display	0,1 °C
	Accuracy	±0,5 °C
Absolute pressure	Measurement range	300...1.200 hPa
	Resolution, display	0,1 hPa
	Accuracy	±3 hPa
Relative Humidity	Measurement range	20...80 % r.H.
	Resolution, display	0,1 % r.H.
	Accuracy	±5 % r.H.
Device data	Power supply	230 V AC, 50 Hz
	max. power consumption	6,5 A
	Dimensions (W x H x D)	571 x 726 x 170 mm
	Weight	11,4 kg
	Interfaces	WLAN
	Connections	Power cable, differential pressure hoses
	Storage temperature	-20...50 °C
	Working temperature	5...40 °C
	Recommended calibration interval	annually
	Sealing canvas	Dimensions
Opening for fan		Ø 525 mm
Large clamps	Clamp length	220 mm
	Weight	0,155 kg
	Dimensions (W x H x D)	220 x 50 x 141 mm
Small clamps	Clamp length	120 mm
	Weight	0,067 kg
	Dimensions (W x H x D)	120 x 48 x 124 mm
Mounting frame	Min. installation opening	0,8 x 0,9 m
	Max. installation opening	1,25 x 2,3 m
	Weight	12 kg
App	Supported operating systems	Android (from 4.0.3) / iOS (from 6.1)

# WÖHLER

**Wöhler Technik GmbH**  
**Headquarters Germany**

Wöhler-Platz 1 · 33181 Bad Wünnenberg  
[www.woehler-international.com](http://www.woehler-international.com)